



Fuse-link, LV, 1.8 A, AC 600 V, 21 x 57 mm, J, UL, time-delay



Part no. LOW-PEAK CLASS J T/D
Catalog No. LPJ-1-8/10SP

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	1.8
Rated voltage			AC 600 V
Size			21 x 57 mm
Utilization category			J
Breaking Capacity		kA	300
Release characteristic	class		time-delay
Standard/Approval			UL
Time delay			time-delay 10 seconds (minimum) at 500% of rated current

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	1.8
Rated voltage		V	600
Voltage type			AC/DC
Rated switching capacity		kA	300
Utilization category			Other
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

Additional product information (links)

Product datasheet (PDF)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_1006_LPJ_0-60.pdf
Product overview (WEB)	http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/fuses_class_cc_j_rk1_rk5/class_j/lpj-sp.html